

View Online at <https://aerobasegroup.com/nsn/5930-01-010-7646>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.250 inches

**Body Length:**

0.750 inches

**Body Width:**

0.345 inches

**Body Height:**

0.515 inches

**Unthreaded Mounting Hole Diameter:**

0.089 inches

**Actuator Style:**

Round

**Actuator Height:**

0.061 inches

**Actuator Free Position Height:**

0.431 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.5 ounces

**Switch Actuating Force:**

14.0 ounces

**Actuator Movement:**

0.016 pretravel inches and 0.007 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes motor dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0