

View Online at <https://aerobasegroup.com/nsn/5930-01-011-3411>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.094 inches

**Body Width:**

0.400 inches

**Body Height:**

0.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.810 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.870 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

14.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.040 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes inductive dc and 6.000 amperes motor dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0