

View Online at <https://aerobasegroup.com/nsn/5930-01-011-4768>

Hazardous Locations/environmental Protection:

Dustproof and watertight

Overall Length:

2.953 inches

Overall Height:

3.344 inches

Overall Width:

1.000 inches

Body Height:

2.641 inches

Unthreaded Mounting Hole Diameter:

0.161 inches

Longest Horizontal Distance Between Mounting Centers:

2.375 inches

Longest Vertical Distance Between Mounting Centers:

0.500 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

7.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+425.00 actuation point pounds per square inch and +100.00/+425.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

280.00 actuation point pounds per square inch and 280.00 deactuation point pounds per square inch gage and 205.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

277.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0