

View Online at <https://aerobasegroup.com/nsn/5930-01-011-5334>

Overall Length:

1.750 inches

Outside Diameter:

0.195 inches all connections and 0.205 inches all connections

Overall Height:

0.478 inches

Overall Width:

1.312 inches

Body Length:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Longest Horizontal Distance Between Mounting Centers:

0.719 inches

Longest Vertical Distance Between Mounting Centers:

0.719 inches

Pressure Switch Type:

Differential

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

15.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

10.0 milliamperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

12.00 actuation point inches of water

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Barbed, unthreaded external all connections

Media For Which Designed:

Gas

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0