

View Online at <https://aerobasegroup.com/nsn/5930-01-011-7687>

Thread Class:

2a single mounting facility

Thread Length:

0.365 inches single mounting facility and 0.385 inches single mounting facility

Overall Length:

3.765 inches

Overall Height:

1.500 inches

Overall Width:

1.430 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.870 inches single actuator and 1.880 inches single actuator

Nonturn Device Radius:

0.427 inches at 3:00 o'clock and 0.447 inches at 3:00 o'clock

Individual Section Quantity:

2

Knob Manufacturer Code:

71590

Knob Manufacturer Part Number:

P-120

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section front

Throw Quantity:

2 each section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

6.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

5.5 amperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Terminals and contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0