

View Online at <https://aerobasegroup.com/nsn/5930-01-012-1322>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.187 inches

**Overall Height:**

5.281 inches

**Overall Width:**

2.593 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Mounting Facility Centers:**

4.625 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Electrical access port and tamper proof cap

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

2000.00 pounds per square inch

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load fourth voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+4.00/+85.00 actuation point pounds per square inch and +3.00/+81.50 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

6.0 dc at sea level fourth voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0