

View Online at <https://aerobasegroup.com/nsn/5930-01-012-1322>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.187 inches

Overall Height:

5.281 inches

Overall Width:

2.593 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

4.625 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port and tamper proof cap

Contact Action Stimulus:

Increase

Proof Pressure:

2000.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+4.00/+85.00 actuation point pounds per square inch and +3.00/+81.50 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

6.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0