

View Online at <https://aerobasegroup.com/nsn/5930-01-012-1339>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.340 inches and 0.360 inches

**Body Length:**

0.510 inches

**Body Width:**

Between 0.460 inches and 0.480 inches

**Body Height:**

Between 0.385 inches and 0.405 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.119 inches and 0.139 inches

**Actuator Height:**

Between 0.632 inches and 0.652 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0