

View Online at <https://aerobasegroup.com/nsn/5930-01-012-3912>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Bushing Length:

0.470 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

0.930 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive dc and 15.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes lamp ac

Test Data Document:

81349-mil-dtl-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0