

View Online at <https://aerobasegroup.com/nsn/5930-01-012-4360>

Overall Length:

7.250 inches

Overall Height:

3.375 inches

Body Diameter:

5.750 inches

Pressure Switch Type:

Differential

Width Across Flats:

0.562 inches

Mounting Method:

Flange and threaded hole

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Contact Load Current Rating:

0.3 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable

Contact Adjustment Range:

+1.00/+35.00 actuation point pounds per square inch and +1.00/+35.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Stimulus Rating:

4.00 differential point ounces per square inch

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Special Features:

Brass bourdon tubes, 0.5 in. Conduit for electrical connection

Style Designator:

Cylindrical w/port

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0