## NSN 5930-01-012-7998

Sensitive Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5950-01-012-7996
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.872 inches and 0.878 inches
Body Length:
Between 1.079 inches and 1.109 inches
Body Width:
0.400 inches
Body Height:
0.626 inches
Unthreaded Mounting Hole Diameter:
Between 0.113 inches and 0.116 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.403 inches and 0.409 inches
Actuator Length:
1.030 inches
Actuator Style:
Leaf
Actuator Width:
0.170 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 grams
Switch Actuating Force:
25.0 grams
Actuator Movement:
Between 0.250 pretravel inches and 0.020 overtravel inches and 0.008 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
3 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:

## NSN 5930-01-012-7998

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0