

View Online at <https://aerobasegroup.com/nsn/5930-01-012-7998>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

Body Length:

Between 1.079 inches and 1.109 inches

Body Width:

0.400 inches

Body Height:

0.626 inches

Unthreaded Mounting Hole Diameter:

Between 0.113 inches and 0.116 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.403 inches and 0.409 inches

Actuator Length:

1.030 inches

Actuator Style:

Leaf

Actuator Width:

0.170 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 grams

Switch Actuating Force:

25.0 grams

Actuator Movement:

Between 0.250 pretravel inches and 0.020 overtravel inches and 0.008 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0