

View Online at <https://aerobasegroup.com/nsn/5930-01-012-8135>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.750 inches

Overall Height:

2.751 inches

Overall Width:

0.750 inches

Body Length:

0.688 inches

Body Width:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.090 inches

Actuator Width:

0.620 inches

Actuator Color:

Red single actuator and red single actuator

Illuminated Actuator Color:

Red single actuator and red single actuator

Actuator Inscription:

On of single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0