NSN 5930-01-012-8143

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-012-8143

- **Body Style:**
- Panel mounted
- **Overall Length:**
- 2.968 inches
- **Overall Height:**
- 1.200 inches
- **Overall Width:**
- 0.960 inches
- **Body Width:**
- 0.960 inches
- **Body Height:**
- 1.200 inches
- **Case Material:**
- Metal
- Actuator Length:

1.040 inches

- Actuator Style:
- Rectangular
- Actuator Height:
- 0.140 inches
- Actuator Width:
- 0.800 inches
- Actuator Color:
- Green single actuator and red single actuator

Illuminated Actuator Color:

Green single actuator and red single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator green lower half of actuator red

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.828 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes

inductive ac and 1.500 amperes lamp ac

Special Features:

Horizontally split lens

NSN 5930-01-012-8143

Push Switch - Page 2 of 2



Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
5 tab, solder lug and 6 turret
Specification Data:
81349-mil-s-22885/9 government specification
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fiig:
A053a0