

View Online at <https://aerobasegroup.com/nsn/5930-01-012-9024>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

Between 0.342 inches and 0.362 inches

Body Length:

Between 0.495 inches and 0.505 inches

Body Width:

Between 0.250 inches and 0.270 inches

Body Height:

Between 0.340 inches and 0.360 inches

Case Material:

Plastic

Actuator Style:

Rectangular

Actuator Height:

Between 0.438 inches and 0.458 inches

Actuator Width:

Between 0.195 inches and 0.205 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 24.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0