# NSN 5930-01-012-9029

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-012-9029

## **Unthreaded Mounting Hole Diameter:**

0.281 inches single mounting facility

## Individual Section Quantity:

1

## Longest Horizontal Distance Between Mounting Centers:

3.000 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

5.500 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

#### **Features Provided:**

Actuator knob

#### Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

#### Mounting Facility Pattern:

Four position rectangular single mounting facility

#### Switch Actuator Indexing Position Quantity:

3 single actuator

## **Terminal Type:**

Screw

#### Switch Actuator Positioning Increment:

60.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

750.0 milliamperes resistive load highest ac voltage rating at sea level

#### **Special Features:**

Green indicator in position one

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A052b0