NSN 5930-01-013-3775

Pressure Switch - Page 1 of 2

400.0 single voltage



View Online at https://aerobasegroup.com/nsn/5930-01-013-3775

Overall Length:
4.680 inches
Overall Height:
6.680 inches
Overall Width:
2.710 inches
Body Height:
3.430 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Longest Vertical Distance Between Mounting Centers:
3.100 inches
Pressure Switch Type:
Gage
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
400.0 milliamperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+15.00/+50.00 actuation point pounds per square inch and +12.00/+47.00 deactuation point pounds per square inch
Contact Adjustment Type:
Internal deactuation point screw and internal actuation point screw
Contact Stimulus Rating:
3.00 differential point pounds per square inch
Contact Voltage Rating In Volts:
480.0 ac at sea level first voltage
Frequency In Hertz:

NSN 5930-01-013-3775

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0