## NSN 5930-01-013-3785

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-013-3785

| Body Style:   |
|---|
| Hole mounted  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                 |
| 1.000 inches  |
| Body Length:  |
| 1.940 inches  |
| Body Width:   |
| 0.687 inches  |
| Body Height:  |
| 0.950 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.173 inches  |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| 0.156 inches  |
| Actuator Free Position Height:  |
| 0.625 inches  |
| Maximum Voltage Rating In Volts:  |
| 480.0 ac and 250.0 dc   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Unthreaded hole   |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit                           |
| Switch Release Force:   |
| 4.0 ounces  |
| Switch Actuating Force:   |
| 15.0 ounces   |
| Actuator Movement:  |
| Between 0.015 pretravel inches and 0.005 overtravel inches and 0.0004 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage:                                     |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac                         |
| Terminal Type And Quantity:   |
| 3 screw   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## **NSN 5930-01-013-3785** Sensitive Switch - Page 2 of 2



Fiig:

A053a0