

View Online at <https://aerobasegroup.com/nsn/5930-01-013-4508>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.814 inches

Overall Height:

2.813 inches

Overall Width:

2.813 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section rear

Throw Quantity:

2 single section rear

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0