

View Online at <https://aerobasegroup.com/nsn/5930-01-013-7289>

Thread Class:

2a single mounting facility

Thread Length:

0.550 inches single mounting facility and 0.610 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.330 inches

First Flat Length:

0.350 inches 1st actuator and 0.410 inches 1st actuator

Flat Height:

0.215 inches 1st actuator and 0.225 inches 1st actuator

Shaft Diameter:

0.248 inches 1st actuator and 0.252 inches 1st actuator

Shaft Length:

1.580 inches 2nd actuator

Overall Diameter:

1.200 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

22.5 degrees from nonturn device 1st actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

8 1st actuator

Shaft Type:

Round, hollowed, flatted 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 3.0 amperes inductive load dc at sea level

Special Features:

Second shaft used for potentiometer

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0