

View Online at <https://aerobasegroup.com/nsn/5930-01-013-8997>

**Overall Length:**

Between 1.250 inches and 1.282 inches

**Overall Height:**

0.688 inches

**Overall Width:**

Between 0.375 inches and 0.406 inches

**Mounting Slot Width:**

0.188 inches

**Body Length:**

0.750 inches

**Body Width:**

0.344 inches

**Body Height:**

0.500 inches

**Distance Between Mounting Facility Centers:**

1.000 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -62.0 degrees celsius and 85.0 degrees celsius

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable, preset

**Contact Adjustment Range:**

+50.00/+105.00 actuation point degrees celsius

**Contact Adjustment Type:**

External actuation point screw

**Contact Stimulus Rating:**

87.00 actuation point degrees celsius and 93.00 actuation point degrees celsius

**Contact Voltage Rating In Volts:**

32.0 dc at sea level second voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Case surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular w/bracket

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0