

View Online at <https://aerobasegroup.com/nsn/5930-01-014-2293>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

9.250 inches

**Overall Height:**

4.125 inches

**Overall Width:**

4.375 inches

**First Flat Length:**

0.250 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.125 inches single actuator

**Individual Section Quantity:**

19

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

B

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

4 each section front

**Mounting Facility Circle Radius:**

1.610 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Shaft Flat/slot Angular Location:**

45.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks 3rd section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 milliamperes resistive load highest ac voltage rating at sea level

**Special Features:**

Sections 1, 2, 3, 7, 11, 12, 13, 16, 17, and 18 make at 2 positions on 1 throw, contact switching action at section 13 shorting, 14 and 15 nonshorting, 16, 17, and 18 shorting, 19 nonshorting

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0