

View Online at <https://aerobasegroup.com/nsn/5930-01-014-2956>

**Body Style:**

Bushing mount

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.540 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.434 inches

**Actuator Height:**

Between 0.940 inches and 0.960 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked in

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc

**Special Features:**

28v dc solenoid will maintain actuator in any of the three positions @when energized

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 turret and 2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0