## NSN 5930-01-014-7887

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-014-7887 **Thread Class:** 2b single mounting facility **Hazardous Locations/environmental Protection:** Explosion proof **Overall Length:** 3.563 inches **Overall Height:** 2.813 inches **Overall Width: 2.813 inches Individual Section Quantity:** 2 **Knob Manufacturer Code:** 82121 **Knob Manufacturer Part Number: Longest Horizontal Distance Between Mounting Centers:** 2.296 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.296 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section front **Throw Quantity:** 3 each section front **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 lowest dc voltage rating at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator

**Shaft Type:** 

Rectangular/square, threaded hole single actuator

## NSN 5930-01-014-7887

Rotary Switch - Page 2 of 2



Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Makes before breaks each section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load lowest ac voltage rating at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0