

View Online at <https://aerobasegroup.com/nsn/5930-01-014-9530>

Thread Class:

2a single threaded bushing

Overall Length:

5.000 inches

Overall Height:

3.812 inches

Overall Width:

1.562 inches

Body Length:

3.813 inches

Pressure Switch Type:

Gage

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

14 single threaded bushing

Contact Action Stimulus:

Increase

Proof Pressure:

6000.00 pounds per square inch

Thread Size:

1.000 inches single threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

500.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+325.00/+4800.00 actuation point pounds per square inch and +240.00/+4715.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Special Features:

Stainless steel material

Frequency In Hertz:

400.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Bourdon tube, open frame

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0