

View Online at <https://aerobasegroup.com/nsn/5930-01-014-9542>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

Between 0.658 inches and 0.718 inches

Bushing Length:

Between 0.856 inches and 0.916 inches

Body Length:

1.916 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.120 inches and 0.130 inches

Actuator Height:

0.204 inches

Actuator Free Position Height:

Between 1.060 inches and 1.120 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.150 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0