

View Online at <https://aerobasegroup.com/nsn/5930-01-014-9543>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.997 inches and 1.003 inches

Body Length:

1.383 inches

Body Width:

0.740 inches

Body Height:

0.950 inches

Unthreaded Mounting Hole Diameter:

0.142 inches

Actuator Length:

Between 0.499 inches and 0.502 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 0.633 inches and 0.647 inches

Actuator Roller Diameter:

Between 0.209 inches and 0.213 inches

Actuator Roller Width:

Between 0.154 inches and 0.158 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.075 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0