

View Online at <https://aerobasegroup.com/nsn/5930-01-014-9543>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Shock resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.997 inches and 1.003 inches

**Body Length:**

1.383 inches

**Body Width:**

0.740 inches

**Body Height:**

0.950 inches

**Unthreaded Mounting Hole Diameter:**

0.142 inches

**Actuator Length:**

Between 0.499 inches and 0.502 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 0.633 inches and 0.647 inches

**Actuator Roller Diameter:**

Between 0.209 inches and 0.213 inches

**Actuator Roller Width:**

Between 0.154 inches and 0.158 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

48.0 ounces

**Actuator Movement:**

Between 0.040 pretravel inches and 0.075 overtravel inches and 0.040 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 1.000 amperes inductive dc and 2.000 amperes lamp dc

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0