

View Online at <https://aerobasegroup.com/nsn/5930-01-014-9545>

Body Style:

Panel mount

Body Length:

Between 0.785 inches and 0.815 inches

Body Width:

Between 0.785 inches and 0.815 inches

Body Height:

Between 2.410 inches and 2.470 inches

Actuator Length:

Between 0.669 inches and 0.699 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.040 inches and 0.100 inches

Actuator Width:

Between 0.669 inches and 0.699 inches

Illuminated Actuator Color:

Yellow single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

17 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0