NSN 5930-01-015-0019

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-015-0019

Body Style:
Bushing mount
Hazardous Locations/environmental Protection:
Moisture resistant
Overall Length:
1.336 inches
Overall Height:
2.359 inches
Overall Width:
1.015 inches
Bushing Length:
0.469 inches
Body Length:
1.336 inches
Body Width:
1.015 inches
Actuator Style:
Round
Actuator Diameter:
0.240 inches
Actuator Height:
0.687 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Support equipment, b-1 aircraft; integrated launch & recovery tv surveillance sys (ilarts); integrated underwater surveillance systems;
nimitz class cvn; catapult/arresting gear; los angeles class ssn (688); test set electronic sys; direct support (dsests); forrestal class cv;
sonar, an/bsy- (v); aircraft, airlifter c-17a
Mounting Surface To Terminal End Distance:
1.203 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches

2 pole, double throw, both positions maintained single switch unit

Nonpile-up Contact Arrangement:

NSN 5930-01-015-0019

Toggle Switch - Page 2 of 2



	ritica	litv	Code	Justifi	cation:
·	ııııca	IILV	Coue	Justill	cation.

Feat

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Special Features:

Weapons system essential

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms14002 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0