

View Online at <https://aerobasegroup.com/nsn/5930-01-015-1298>

Thread Class:

3b first pressure connection

Overall Length:

4.120 inches

Overall Height:

1.870 inches

Overall Width:

3.625 inches

Body Diameter:

1.620 inches

Mounting Slot Width:

0.196 inches

Body Length:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.196 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

0.620 inches

Pressure Switch Type:

Absolute

Mounting Method:

Unthreaded hole and flange

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Sensing Element Burst Pressure:

7500.00 pounds per square inch gage

Terminal Type:

Wire lead

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+800.00/+1400.00 actuation point pounds per square inch gage and +800.00/+1400.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

1000.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0