

View Online at <https://aerobasegroup.com/nsn/5930-01-015-3600>

Overall Height:

Between 0.950 inches and 0.990 inches

Overall Width:

1.187 inches

Body Thickness:

Between 0.229 inches and 0.239 inches

Unthreaded Mounting Hole Diameter:

0.093 inches single mounting facility and 0.097 inches single mounting facility

Longest Horizontal Distance Between Mounting Centers:

0.812 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

2 single section front

Throw Quantity:

6 single section front

Mounting Method:

Strut single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Style Designator:

Switch section, rotary

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0