

View Online at <https://aerobasegroup.com/nsn/5930-01-015-3600>

**Overall Height:**

Between 0.950 inches and 0.990 inches

**Overall Width:**

1.187 inches

**Body Thickness:**

Between 0.229 inches and 0.239 inches

**Unthreaded Mounting Hole Diameter:**

0.093 inches single mounting facility and 0.097 inches single mounting facility

**Longest Horizontal Distance Between Mounting Centers:**

0.812 inches single mounting facility

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

2 single section front

**Throw Quantity:**

6 single section front

**Mounting Method:**

Strut single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

**Style Designator:**

Switch section, rotary

**Test Data Document:**

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0