# NSN 5930-01-015-5246

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-015-5246

#### **Thread Length:**

0.469 inches single mounting facility

#### **Overall Length:**

4.750 inches

# First Flat Length:

0.437 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.625 inches single actuator

#### **Overall Diameter:**

2.000 inches

#### Individual Section Quantity:

7

# Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

1 each section front

### Throw Quantity:

8 each section front

# Mounting Method:

Threaded bushing single mounting facility

#### **Features Provided:**

Actuator knob

# Thready Qty Per Inch (tpi):

32 single mounting facility

# Thread Size:

0.469 inches single mounting facility

# Contact Voltage Rating In Volts:

30.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

8 single actuator

#### Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Screw

# **Contact Switching Action:**

Breaks before makes each section front

# Switch Actuator Positioning Increment:

45.0 degrees single actuator

# NSN 5930-01-015-5246

Rotary Switch - Page 2 of 2



### **Contact Load Current Rating:**

5.0 amperes resistive load lowest ac voltage rating at sea level

#### Style Designator:

Tap, circular, bushing mount

#### **Thread Series Designator:**

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

#### Fiig:

A052b0