

View Online at <https://aerobasegroup.com/nsn/5930-01-015-6373>

Thread Length:

0.380 inches single mounting facility

Overall Length:

1.790 inches

First Flat Length:

0.230 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.310 inches single actuator

Overall Diameter:

1.375 inches

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3:00 o'clock

End Application:

Ticonderoga class cg (47), virginia class cgn (41), nimitz class cvn, spruance class dd (963), Forrestal class cv, Kidd class ddg, radar set It air traffic control (17m Jul83)(an/tps-63), radar set, lightweight 3d (an/tps-59), interrogator set (a0681) (an/upx-27).

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Shaft Flat/slot Angular Location:

15.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Special Features:

Weapon system essential

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0