

View Online at <https://aerobasegroup.com/nsn/5930-01-015-6373>

**Thread Length:**

0.380 inches single mounting facility

**Overall Length:**

1.790 inches

**First Flat Length:**

0.230 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.310 inches single actuator

**Overall Diameter:**

1.375 inches

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 3:00 o'clock

**End Application:**

Ticonderoga class cg (47), virginia class cgn (41), nimitz class cvn, spruance class dd (963), Forrestal class cv, Kidd class ddg, radar set It air traffic control (17m Jul83)(an/tps-63), radar set, lightweight 3d (an/tps-59), interrogator set (a0681) (an/upx-27).

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Shaft Flat/slot Angular Location:**

15.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Special Features:**

Weapon system essential

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0