

View Online at <https://aerobasegroup.com/nsn/5930-01-015-7412>

Hazardous Locations/environmental Protection:

Moisture resistant and explosion proof

Overall Length:

3.760 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

3.590 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

12 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level 125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 each section

Contact Arrangement Truth Table:

Decimal, 1 pole - 12 positions each section

Color:

Black each body black each indicator background white each indicator marking

Precious Material And Location:

Printed circuit board surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0