Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-015-7599

| Hazardous Locations/environmental Protection: |
|--|
| Dustproof |
| Overall Length: |
| 0.350 inches |
| Overall Height: |
| 1.255 inches |
| Overall Width: |
| 1.212 inches |
| Individual Section Quantity: |
| 1 |
| Operating Tempurature Range: |
| -30.0/+85.0 degrees celsius |
| Mounting Method: |
| Strut single mounting facility |
| Actuator Type: |
| Push button single actuator |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 10 single actuator |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Printed circuit |
| Contact Load Current Rating: |
| 50.0 milliamperes resistive load dc at sea level |
| Readout Indicator Marking: |
| 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section |
| Contact Arrangement Truth Table: |
| Complement of 9's complement, 1 pole - 10 positions single section |
| Special Features: |
| Decimal point located on front of module |
| Color: |
| White single indicator marking |
| Precious Material And Location: |
| Printed circuit board surfaces gold |
| Precious Material: |
| Gold |
| Style Designator: |
| Rectangular indicating |
| Shelf Life: |
| N/a |

Code Indicating Wheel Switch - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0