

View Online at <https://aerobasegroup.com/nsn/5930-01-016-0510>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

Between 0.985 inches and 1.015 inches

Bushing Length:

Between 0.465 inches and 0.485 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 1.130 inches and 1.190 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

2.030 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Magnetic hold-in for down position

Test Data Document:

81349-mils5594 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0