## NSN 5930-01-016-2499

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-016-2499

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
4.751 inches
Overall Height:
2.906 inches
Overall Width:
2.813 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
В
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
1 single section front
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Criticality Code Justification:
Feat
Terminal Type:
Screw

## **NSN 5930-01-016-2499**Rotary Switch - Page 2 of 2

Fiig: A052b0



Contact Switching Action:
Breaks before makes single section front
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load highest ac voltage rating at sea level
Special Features:
Item must comply with requirements of desc production standard no. L01999, for navy nuclear propulsion plant products only
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No