

View Online at <https://aerobasegroup.com/nsn/5930-01-016-6071>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.375 inches 1st mounting facility

Overall Length:

4.500 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.210 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

7

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Operating Temperature Range:

+0.0/+5.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

12 each section rear

Mounting Facility Circle Radius:

0.900 inches 2nd mounting facility

Mounting Method:

Threaded stud 2nd mounting facility

Thready Qty Per Inch (tpi):

32 1st mounting facility

Thread Size:

0.469 inches 1st mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Mounting Facility Pattern:

Four position circular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0