

View Online at <https://aerobasegroup.com/nsn/5930-01-016-7092>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.186 inches and 0.190 inches

**Body Length:**

Between 0.550 inches and 0.610 inches

**Body Width:**

Between 0.190 inches and 0.210 inches

**Body Height:**

Between 0.425 inches and 0.475 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.187 inches

**Actuator Style:**

Round

**Actuator Width:**

0.090 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

16.0 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes resistive ac and 5.000 amperes inductive ac

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0