

View Online at <https://aerobasegroup.com/nsn/5930-01-016-7092>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Moisture resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.186 inches and 0.190 inches

Body Length:

Between 0.550 inches and 0.610 inches

Body Width:

Between 0.190 inches and 0.210 inches

Body Height:

Between 0.425 inches and 0.475 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.187 inches

Actuator Style:

Round

Actuator Width:

0.090 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0