## NSN 5930-01-017-2232

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-017-2232

| Body Style:   |
|---|
| Hole mounted  |
| Hazardous Locations/environmental Protection:   |
| Weatherproof  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                       |
| 0.375 inches  |
| Body Length:  |
| 0.781 inches  |
| Body Width:   |
| 0.250 inches  |
| Body Height:  |
| 0.395 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.088 inches  |
| Actuator Style:   |
| Round   |
| Actuator Diameter:  |
| 0.068 inches  |
| Actuator Free Position Height:  |
| 0.350 inches  |
| Maximum Voltage Rating In Volts:  |
| 125.0 ac and 30.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, double throw, one position momentary single switch unit                                 |
| Switch Release Force:   |
| 1.0 ounces  |
| Switch Actuating Force:   |
| 7.5 ounces  |
| Actuator Movement:  |
| Between 0.020 pretravel inches and 0.005 overtravel inches and 0.004 differential inches        |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac |
| Terminal Type And Quantity:   |
| 3 solder stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## **NSN 5930-01-017-2232** Sensitive Switch - Page 2 of 2



Fiig:

A053a0