Rotary Switch - Page 1 of 2

5

G



View Online at https://aerobasegroup.com/nsn/5930-01-017-5086

Hazardous Locations/environmental Protection: Explosion proof **Overall Length:** 6.250 inches **Overall Height:** 2.906 inches **Overall Width:** 2.812 inches **Individual Section Quantity:** Knob Manufacturer Code: 82121 **Knob Manufacturer Part Number:** Longest Horizontal Distance Between Mounting Centers: 2.000 inches single mounting facility Shortest Horizontal Distance Between Mounting Centers: 1.000 inches single mounting facility Longest Vertical Distance Between Mounting Centers: 2.188 inches single mounting facility Switch Contact Basic Design: Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 7 each section front **Mounting Method:** Bracket single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 500.0 highest ac voltage rating at sea level **Mounting Facility Pattern:** Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator

NSN 5930-01-017-5086

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0