NSN 5930-01-017-5934

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-017-5934

View Online at https://aerobasegroup.com/nsn/5930-01-017-5934
Overall Length:
3.285 inches
Outside Diameter:
0.213 inches all connections and 0.219 inches all connections
Overall Height:
3.279 inches
Body Diameter:
3.220 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Longest Horizontal Distance Between Mounting Centers:
0.500 inches
Longest Vertical Distance Between Mounting Centers:
1.240 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
10.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
8.75 actuation point inches of water and 4.10 deactuation point inches of water and 4.65 differential point inches of water
Contact Voltage Rating In Volts:
250.0 ac at sea level first voltage
Pressure Connector Type:
Plain, unthreaded external single connection
Media For Which Designed:
Liquid
Style Designator:
Cylindrical w/bracket

N/a

Shelf Life:

NSN 5930-01-017-5934

Pressure Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A048b0