

View Online at <https://aerobasegroup.com/nsn/5930-01-017-5934>

Overall Length:

3.285 inches

Outside Diameter:

0.213 inches all connections and 0.219 inches all connections

Overall Height:

3.279 inches

Body Diameter:

3.220 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Longest Horizontal Distance Between Mounting Centers:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

1.240 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

10.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

8.75 actuation point inches of water and 4.10 deactuation point inches of water and 4.65 differential point inches of water

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Plain, unthreaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0