

View Online at <https://aerobasegroup.com/nsn/5930-01-017-5938>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Watertight

Bushing Length:

Between 0.304 inches and 0.320 inches

Body Length:

0.531 inches

Body Width:

0.283 inches

Body Height:

Between 0.395 inches and 0.425 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.212 inches and 0.216 inches

Actuator Height:

Between 0.640 inches and 0.660 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0