

View Online at <https://aerobasegroup.com/nsn/5930-01-017-8220>

Overall Length:

6.300 inches

Overall Height:

3.100 inches

Overall Width:

4.750 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

7500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

6.0 amperes resistive load fourth voltage and 5.0 amperes inductive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+2500.00/+5000.00 actuation point pounds per square inch and +1700.00/+4200.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point serrated nut and internal deactuation point serrated nut

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Frequency In Hertz:

50.0 third voltage and 60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0