

View Online at <https://aerobasegroup.com/nsn/5930-01-018-1471>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight

Switch Actuator Quantity:

1

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

1.745 inches

Housing Length:

4.204 inches

Housing Width:

1.620 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.156 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

64.0 inch-ounces

Actuator Movement:

Between 15.0 pretravel degrees and 60.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 1.200 amperes inductive ac

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0